AUTHOR: Lazarev, V. B.   SOV/78-3-10-20/35

TITLE: On the Surface Tension of Ternary Systems (O poverkhnostnom natyazhenii troynykh sistem)

PERIODICAL: Zhurnal neorganicheskoy khimii, 1958, Vol 3, Nr 10, pp 2347-2353 (USSR)

ABSTRACT: The term of the limit surface activity was introduced for the ternary systems. The surface tension of the ternary systems in dependence on the concentration of the independent components was presented by the equations 11 and 11a.

$$\left(\frac{\partial \sigma}{\partial c_{N_1}}\right)_{c_{N_2}} = - \frac{RTN}{\omega} \left[\frac{(e^{\Delta_2}-1)c_{N_2}\frac{\partial f_2}{\partial c_{N_1}} + (e^{\Delta_1}-1) + c_{N_1}(e^{\Delta_1}-1)\cdot\frac{\partial f_1}{\partial c_{N_1}}}{1 + (e^{\Delta_1}-1)c_{N_1} + (e^{\Delta_2}-1)c_{N_2}} \right] \quad (11)$$

Card 1/4

On the Surface Tension of Ternary Systems

$$\left(\frac{\partial \sigma}{\partial c_{N_2}}\right)_{c_{N_1}} = -\frac{RTN}{\omega}\left[\frac{(e^{\Delta_1}-1)c_{N_1}\frac{\partial f_1}{\partial c_{N_2}} + (e^{\Delta_2}-1)+c_{N_2}(e^{\Delta_2}-1)\frac{\partial f_2}{\partial c_{N_2}}}{1 + (e^{\Delta_1}-1)c_{N_1} + (e^{\Delta_2}-1)c_{N_2}}\right] \quad (11a)$$

The following equations (12) and (12a) were given for the ternary systems, taking into account the limit values of surface activity G_{o1} and G_{o2}:

$$G_{o1} = \lim_{c_{N_1} \to o} \left(-\frac{\partial \sigma}{\partial c_{N_1}}\right)_{c_{N_2}} = \frac{RTN}{\omega}\left[\frac{(e^{\Delta_2}-1)c_{N_2}\cdot\frac{\partial f_2}{\partial c_{N_1}} - (e^{\Delta_1}-1)}{1 + (e^{\Delta_2}-1)c_{N_2}}\right] \quad (12)$$

$$G_{o2} = \lim_{c_{N_2} \to o} \left(-\frac{\partial \sigma}{\partial c_{N_2}}\right)_{c_{N_1}} = \frac{RTN}{\omega}\left[\frac{(e^{\Delta_1}-1)c_{N_1}\cdot\frac{\partial f_1}{\partial c_{N_2}} + (e^{\Delta_2}-1)}{1 + (e^{\Delta_1}-1)c_{N_1}}\right] \quad (12a)$$

Card 2/4

SOV/78-3-10-20/35

On the Surface Tension of Ternary Systems

The limit values of the surface activity of cadmium, potassium and cesium in solutions of mercury-cadmium-potassium and mercury-cadmium-cesium were calculated by the graphic method. From the equation 12 follows that the limit values of surface tension of potassium and cesium are increased with the increase in concentration of the cadmium. On the basis of the results obtained for the surface tension of mercury-cadmium-potassium solutions and mercury-cadmium-cesium solutions at 22°C the adsorption of alkali metals in ternary solutions was calculated for three constant concentrations of cadmium and potassium. It was demonstrated that the adsorption of cadmium metals passes through maximum values. The dependence of the adsorption of urethan in the system sodium chloride-urethan-water on the concentration of urethan was investigated at three different concentrations of sodium chloride. All the rules governing the adsorption, which were determined by the investigations of mercury-cadmium-potassium and mercury-cadmium-cesium solutions, correspond completely to the molecular theory of the limit phenomena of surface tension in solutions.

Card 3/4   There are 8 figures and 9 references, 4 of which are Soviet.

86705

S/076/60/034/011/020/024
B004/B064

11.3950

AUTHORS: Pugachevich, P. P. and Lazarev, V. B. (Moscow)

TITLE: A Device for Measuring the Surface Tension of Melts at
   High Temperatures

PERIODICAL: Zhurnal fizicheskoy khimii, 1960, Vol. 34, No. 11,
                pp. 2607-2609

TEXT: The apparatus shown in Fig. 1 is used to determine the surface
tension of melts at temperatures of up to 1600-1800°C by measuring the
maximum gas bubble pressure. The cylindrical cover 1 is sealed with the
rubber ring 3 and screwed into the plate 5 with the screw bolt 4; the
plate is firmly fixed to the base 6. The stand 7, the upper part of which
is made of refractory material, the lower one of heat-resistant steel, is
connected with 5 through the brass bellow 9, and is lifted by the appliance
5. It is fixed with the screws 13,14. The height of 7 is read by means of
the rod 8 and the nonius 11 which are on plate 12. The crucible 15 with
the substance to be examined 16 stands on the stand. The substance is
molten in a vacuum by means of a cylindrical heater 17 made of a 0.1 mm
Card 1/3

86785

S/076/60/034/011/020/024
B004/B064

A Device for Measuring the Surface
Tension of Melts at High Temperatures

thick tantalum plate which is fed by the power current of an ОСУ-20 (OSU-20)
step-down transformer. The current is supplied through the water-cooled
feeding pipes 18 and 19 which are insulated against 5. The molybdenum
screens 20 on the base 21 are used to prevent thermal radiation. Tempera-
ture is measured either with a thermocouple or with a pyrometer through
the sight hole 27. Two capillaries 25 and 26 of different diameters are
dipped into the melt. By means of lithium heated to 300°C and solid CO_2,
argon purified with alcohol is passed through the capillaries, and the
maximum pressure is determined with a magnetic diaphragm gauge. The sur-
face tension is determined from an equation given by S. Sugden (Ref. 2).
There are 2 figures and 2 non-Soviet references.

ASSOCIATION: Akademiya nauk, Institut obshchey i neorganicheskoy khimii
im. N. S. Kurnakova (Academy of Sciences of the USSR,
Institute of General and Inorganic Chemistry imeni
N. S. Kurnakov)

SUBMITTED: June 27, 1960

Ca   Card 2/3

83564

9,4340

S/020/60/134/001/016/021
B004/B060

AUTHORS: Lazarev, V. B., Pugachevich, P. P.

TITLE: The Temperature Dependence of the Surface Stress of Germanium

PERIODICAL: Doklady Akademii nauk SSSR, 1960, Vol. 134, No. 1, pp. 132 - 133

TEXT: By way of introduction, the authors discuss the data published on the surface stress of germanium and the errors involved in the methods applied. They determined the surface stress by measuring the maximum pressure in a gas bubble according to the theory developed by M. Cantor (Ref. 8). The capillaries required for the purpose were prepared from spectroscopically pure graphite. Germanium single crystals of a resistivity of 20 ohm.cm were heated in a vacuum furnace through which argon was fed. The values for the density of the molten Ge required for the calculation of the surface stress, σ, were taken from Ref. 13, and extrapolated up to 1400°C. The maximum error for σ was 1%. It was found that $\sigma = 621.4 - 0.261(t^o - 936^o)$, where t^o is the temperature in

Card 1/2

83564

The Temperature Dependence of the Surface   S/020/60/134/001/016/021·
Stress of Germanium   B004/B060

degrees centigrade, and 936°C is the melting point of Ge according to
Ref. 14. The value of 621.4 dynes/cm holding for this temperature is in
good agreement with the value calculated by S. N. Zadumkin (617 dynes/cm).
As opposed thereto, the temperature coefficient $d\sigma/dT = -0.21$, de-
termined by the authors experimentally, deviates markedly from Zadumkin's
value (-0.054). This may be due to the structural change of the melt,
which was not considered by Zadumkin. The experimental data are given in
Table 1 and graphically reproduced in Fig. 1. There are 1 figure,
1 table, and 15 references: 9 Soviet, 4 US, 1 British, 1 German, and
1 French.

ASSOCIATION: Institut obshchey i neorganicheskoy khimii im.
               N. S. Kurnakova Akademii nauk SSSR (Institute of General
               and Inorganic Chemistry imeni N. S. Kurnakov of the
               Academy of Sciences USSR)

PRESENTED: April 13, 1960, by I. I. Chernyayev, Academician

SUBMITTED: April 11, 1960

Card 2/2

LAZAREV, V.B.; PUGACHEVICH, P.P.

Limiting surface activity of ternary solutions. Zhur. fiz. khim.
35 no.2:314-318 F '61.   (MIRA 16:7)

1. Institut obshchey i neorganicheskoy khimii imeni Kurnakova
AN SSSR.
   (Systems (Chemistry))   (Surface chemistry)

PUGACHEVICH, P.P.; LAZAREV, V.B.

Empirical study of the surface tension of metallic solutions. Part 3:
Surface phenomena in the ternary matallic solutions Hg – Cd – K and
Hg – Cd – Cs at 22°. Zhur. fiz. khim. 35 no.3:530-534 Mr '61.
                                                    (MIRA 14:3)
1. Akademiya nauk SSSR, Institut obshchey i neorganicheskoy khimii
im. N.S. Kurnakova.
                (Surface tension)   (Amalgams)

TIMOFEYEVICHEVA, O.A.; LAZAREV, V.B.

Temperature dependence of the surface tension of thallium. Dokl.AN SSSR 138 no.2:412-414 My '61.   (MIRA 14:5)

1. Institut obshchey i neorganicheskoy khimii im. N.S.Kurnakova Akademii nauk SSSR. Predstavleno akademikom I.V.Tananayevym.
        (Surface tension)   (Thallium)

33985
S/062/62/000/002/010/013
B117/B138

ll.4110

AUTHORS: Timofeyevicheva, U. A., and Lazarev, V. B.

TITLE: Surface tension of metallic cesium

PERIODICAL: Akademiya nauk SSSR. Izvestiya. Otdeleniye khimicheskikh
              nauk, no. 2, 1962, 358 - 359

TEXT: The surface tension of cesium was repeatedly measured at three
different temperatures with a glass instrument devised by
O. A. Timofeyevicheva and based on the bubble pressure principle. The
following values were found: σ = 67.5 dynes/cm at 62°C; σ = 62.9 dynes/cm
at 146°C; σ = 62.4 dynes/cm at 152°C. These results are in good agreement
with the theoretical data available in the literature. There are 1 figure
and 12 references: 5 Soviet and 7 non-Soviet. The two references to
English-language publications read as follows: E. E. Poindexter,
M. Kernachan, Phys. Rev. 27, 820 (1926); J. W. Taylor, Philos. Mag. 46,
867 (1955).

Card (1/2)

Surface tension of metallic cesium

33985
S/062/62/000/002/010/013
B117/B138

ASSOCIATION: Institut obshchey i neorganicheskoy khimii im. N. S. Kurnakova Akademii nauk SSSR (Institute of General and Inorganic Chemistry imeni N. S. Kurnakov of the Academy of Sciences USSR)

SUBMITTED: February 7, 1961 (initially),
October 26, 1961 (after revision)

Card 2/2

SEMENCHENKO, V.K.; LAZAREV, V.B.

Dependence of the surface tension of ternary solutions on component
concentration and temperature. Izv. AN SSSR. Otd.khim.nauk no.11:
2089-2091 N '62.   (MIRA 15:12)

1. Institut obshchey i neorganicheskoy khimii im. N.S. Kurnakova
AN SSSR.
          (Systems (Chemistry))   (Surface tension)

1.1800

33417

S/032/62/028/002/020/037
B139/B104

AUTHORS: Pugachevich, P. P., and Lazarev, V. B.

TITLE: Tinning of high-melting metals and graphite

PERIODICAL: Zavodskaya laboratoriya, v. 28, no. 2, 1962, 208

TEXT: Oxide films and impurities are removed from band and rod profiles and other parts of tungsten, tantalum, molybdenum, and graphite which are then for some minutes kept in a vacuum furnace at $\sim 10^{-4}$ mm Hg and 1100 - 1200°C, and dipped into molten tin in the same furnace at 1100 - 1200°C. Thus, uniform tinning is guaranteed, and the parts treated can be soldered to copper parts by usual methods. Good adhesion of larger surfaces is reached by joining parts before they are dipped into molten tin under the conditions mentioned. Thus, graphite can be tinned and soldered to parts of high-melting metals by the vacuum dipping method. In tensile strength tests of such joints, cracks occur in the graphite mass. It was also possible to provide graphite with a smooth cadmium coating by vacuum dipping at 450°C. [Abstracter's note: Essentially complete translation.]
Card 1/2

Tinning of high-melting metals...

33417
S/032/62/028/002/020/037
B139/B104

ASSOCIATION: Institut obshchey i neorganicheskoy khimii im. N. S. Kurnakova Akademii nauk SSSR (Institute of General and Inorganic Chemistry im. N. S. Kurnakov of the Academy of Sciences SSSR)

Card 2/2

S/020/62/143/003/023/029
B101/B144

AUTHORS: Timofeyevicheva, O. A., Lazarev, V. B., and Pershikov, A. V.

TITLE: Dependence of surface tension of cesium on temperature

PERIODICAL: Akademiya nauk SSSR. Doklady, v. 143, no. 3, 1962, 618 - 620

TEXT: The surface tension of Cs at 62 - 280°C was measured. As Cs wets the glass well in vacuum and in inert atmosphere the method of maximum pressure in the gas bubble was chosen, and a special apparatus constructed (Fig. 1).   After evacuation of the apparatus ~40 g Cs were distilled in vacuum through the tube 3 into the containers 1 and 2, the apparatus was filled with purified argon up to a pressure of 480 mm Hg, melted at 4,4', and placed in a thermostat.   Turning clockwise in the plane of the figure filled the manometer 5 and the lower part of 6 with Cs, so that the capillary 7 dipped into Cs.   After returning to the original position the metal residue in 2 was led through 8 and 9 into 1 by turning the apparatus round the x-x₁ axis.   The plane of 5 forms a small angle with the symbol plane, so that Cs could not flow out of 5 and 6.   The resulting difference in pressure led to the formation of gas bubbles in capillary 7.

Card 1/3

—rral N. S. Kurnakov of the Academy of
—stitute of General and
Im. N. S.

S/020/62/146/001/015/016
B101/B144

AUTHORS: Lazarev, V. B., Pershikov, A. V.

TITLE: Experimental determination of the surface tension of molten neodymium

PERIODICAL: Akademiya nauk SSSR. Doklady, v. 146, no. 1, 1962, 143 - 144

TEXT: The surface tension, σ, of neodymium freed from neodymium oxide traces by filtering through beryllium oxide and tantalum funnels in $1 \cdot 10^{-5}$ mm Hg vacuum was measured in vacuo by determining the maximum pressure of an argon bubble. The argon was purified by bubbling through molten lithium at $300°C$. Polymethyl-phenyl siloxane vacuum oil was used as manometer liquid. Results: (1) σ is a linear function of temperature, amounting (in dynes/cm) to 688 at $1030°C$ and 674 at $1186°C$. These values are in good agreement with the theoretical value of 600 dynes/cm obtained by S. N. Zadumkin, B. S. Tambiyev (Uch. zap. Kabardino-Balkarsk. gos. univ., .13, 47 (1961)). (2) The curves for surface tension, density, and reciprocal isothermal compressibility versus atomic number show a similar course for the lanthanides. Thus a close relationship exists between

Card 1/2

Experimental determination of...   S/020/62/146/001/015/016
                                          B101/B144

surface and bulk properties of substances. There are 3 figures and 1
table.

ASSOCIATION: Institut obshchey i neorganicheskoy khimii im. N. S.
              Kurnakova Akademii nauk SSSR (Institute of General and
              Inorganic Chemistry imeni N. S. Kurnakov of the Academy
              of Sciences USSR)

PRESENTED: April 2, 1962, by I. V. Tananayev, Academician

SUBMITTED: March 28, 1962

Card 2/2

1015

S/020/62/146/004/010/015
B101/B186

AUTHORS: Lazarev, V. B., Dashevskiy, M. Ya.

TITLE: Surface tension of indium - antimony melts

PERIODICAL: Akademiya nauk SSSR. Doklady, v. 146, no. 4, 1962, 822 - 825

TEXT: The surface tension of 26 In - Sb melts of various concentrations was measured range of 550 - 700°C for the following purposes: (1) to find out whether a singular point in the diagram of surface tension versus com- position corresponds to the singular point in the phase diagram of a given system in which congruently melting InSb is formed, and (2) to obtain data on the surface tension of melts with a non-stoichiometric composition, -such data being of practical importance in pulling InSb single crystals. The authors prepared the specimens according to Czochralski's method. The surface tension σ was determined from the maximum pressure of a gas bubble. The wall of the quartz capillary was ground to a thickness of 0.01 mm to facilitate calculation of σ. The measurement was conducted in an atmos- phere of argon at approximately 100 mm Hg with a maximum total error of 1.2 %, corresponding to ~7.0 dyne/cm. Results: σ_{In} is in good agreement

Card 1/3

Surface tension of indium - ...   S/020/62/146/004/010/015
                                                    B101/B186

PRESENTED: May 20, 1962, by I. I. Chernyayev, Academician

SUBMITTED: May 20, 1962

Card 3/3

ACCESSION NR: AT4030798   S/0000/63/000/000/0125/0132

AUTHOR: Lazarev, V. B.; Dashevskiy, M. Ya.

TITLE: A study of surface phenomena in melts of the In-Sb system

SOURCE: AN UkrSSR. Institut metallokeramiki i spetsial'ny*kh splavov.
Poverkhnostny*ye yavleniya v rasplavakh i protsessakh poroshkovoy metallurgii (sur-
face phenomena in liquid metals and processes in powder metallurgy). Kiev, Izd-vo
AN UkrSSR, 1963, 125-132

TOPIC TAGS: surface phenomenon, indium, antimony, indium based alloy, antimony
containing alloy, surface tension, indium antimonide

ABSTRACT: In this paper the authors presented the results of an investigation of
the concentration and temperature relationships of the surface tension of indium-
antimony system melts with the congruently melted chemical compound indium antimo-
nide. It was explained that a correspondence exists between the spatial points on
the structural diagram of the indium-antimony system and on the diagram surface
tension-composition. In addition, experimental data was obtained on the surface
tension of melts for which the composition does not strongly differ from the
stoichiometric melt of the indium-antimonide compound. A diagram of the instrument

Card 1/2

ACCESSION NR: AT4030798

for determining the surface tension was presented. Results were presented in graphs.
The temperature relationship of the surface tension was studied as the following:
indium (at a temperature range of 200-800°C), antimony (at a temperature range of
650-800°C) and 26 alloys of the indium-antimony system at a temperature range of
550-700°C. It was established that throughout the entire investigated temperature
range, antimony is surface active in relation to indium. It was shown that the
existence of an intermetallic compound in the indium-antimony system finds repre-
sentation in the isotherms of the surface tension in the melts of this system.
Orig. art. has: 6 figures and 2 formulas.

ASSOCIATION: Institut obshchey i neorganicheskoy khimii AN SSSR,   · Moscow
(Institute of General and Inorganic Chemistry, AN SSSR)·

SUBMITTED: 23Nov63   DATE ACQ: 16Apr64   ENCL: 00

SUB CODE: ML ·   NO REF SOV: 012   OTHER: 008

Card 2/2

S/062/63/000/003/015/018
B101/B186

AUTHOR: Lazarev, V. B.

TITLE: Problem of the regularities of the adsorption on metal melts

PERIODICAL: Akademiya nauk SSSR. Izvestiya. Otdeleniye khimicheskikh nauk, no. 3, 1963, 565 - 567

TEXT: In a previous study (Dokl. AN SSSR, 146, 872 (1962)) it was found that the isotherms of the surface tension of In-Sb melts show an inflection in the concentration range, which corresponds to the formation of InSb. Now the adsorption was calculated according to the equation

$$\Gamma_1^N = -(1 - N_1)\partial\sigma/RT\partial\ln a_1.$$

Γ is the adsorption, N_1 the molar part of the component 1, σ the surface tension, a_1 the activity of the component 1.

It was found that Γ passes through two maxima if the Sb content is changed from 0 - 100 at %. One of these lies at 6 at % Sb, the second at 52 at % Sb and there also is a minimum at 50 at % Sb, which is where the stoichiometric composition corresponds to InSb. The maximum at 52 at % Sb and the minimum at 50 at % Sb become gradually flatter with increasing temperature
Card 1/2

Problem of the regularities of ...

S/062/63/000/003/015/018
B101/B186

and at $700^{\circ}C$ they already come within the range of experimental error. From the function $\Gamma = f(a,T)$ the adsorption heat was calculated to be 3.450 kcal/mole at $450^{\circ}C$, i. e. very near to the heat of formation of the InSb. There are 2 figures.

ASSOCIATION: Institut obshchey i neorganicheskoy khimiiiim. N. S. Kurnakova Akademii nauk SSSR (Institute of General and Inorganic Chemistry imeni N. S. Kurnakov of the Academy of Sciences USSR)

SUBMITTED: October 23, 1962

Card 2/2

L 16929-63   EWP(q)/EWT(m)/BDS   AFFTC   JD

S/076/63/037/004/021/029

AUTHOR: Lazarev, V. B., Pershikov, A. V.   56

TITLE: Surface tension of strontium

PERIODICAL: Zhurnal fizicheskoy khimii, V. 37, No. 4, 1963, 907-908

TEXT: The surface tension of melted strontium in the range from 775-883
degrees is measured. The method of maximum pressure in a gas bubble with the em-
ployment of two capillaries of different diameters which are set accurately in the
same horizontal plane is used. The experimental data which is obtained agrees
well with the conclusions of the statistical electron theory of surface tension
which was developed by S. N. Zadumkin. There is 1 figure. The most important
English-language reference reads as follows: J. Taylor, Metallurgia, 50 (300),
161, 1954.

ASSOCIATION: Institut obshchey i neorganicheskoy khimii imeni N. S. Kurnakova,
             Akademiya nauk SSSR (Institute of General and Inorganic Chemistry
             imeni N. S. Kurnakov, Academy of Sciences USSR)

SUBMITTED: June 9, 1962

Card 1/1

LAZAREV, V.B.; PERSHIKOV, A.V.

Surface tension of strontium. Zhur. fiz. khim. 37 no.4:907-908
Ap '63.

(MIRA 17:7)

1. Institut obshchey i neorganicheskoy khimii imeni N.S.
Kurnakova AN SSSR.

YASHKICHEV, V.I.; LAZAREV, V.B.

Measurement of the surface tension of electrolytic copper by the method of maximum gas bubble pressure. Izv.AN SSSR. Ser.khim.
no.1:170-172 Ja '64.
(MIRA 17:4)

1. Institut obshchey i neorganicheskoy khimii im. N.S.Kurnakova
AN SSSR.

L 10631-65   EWT(m)/T/EWP(b)   IJP(c)/SSD/AFWL/RAEM(t)   JD
ACCESSION NR: AP4041170   8/0062/64/000/006/1104/1106

AUTHOR: Lazarev, V. B.; Abdusalyamova, M. N.

TITLE: Relationship between the surface tension of thallium sulfide and temperature.   B

SOURCE: AN SSSR. Izv. Seriya khimicheskaya, no. 6, 1964, 1104-1106

TOPIC TAGS: thallium sulfide, surface tension, sulfur, surface active effect

ABSTRACT: The surface tension-temperature relationship of Tl_2S in the 500-700C temperature range was found to be linear: $\sigma = 215.6 - 0.0356\,(t-t_m)$ where t is in degrees C and $T_m = 445C$. Values for the surface tension were obtained from calculation by the Sugden formula

$$\sigma = \frac{1}{2}\,\frac{P_l - P_i}{1/x_1 - 1/x_2} \qquad (1)$$

and the Cantor-Schrodinger formula

Card 1/2

L 10631-65

ACCESSION NR: AP4041170

$$d = \frac{\frac{1}{4}(P_1 - P_2) - \frac{1}{2}\rho(r_1 - r_2)g - \frac{1}{12}\rho^2g^2\left(\frac{r_1^2}{P_1} - \frac{r_2^2}{P_2}\right)}{1/r_1 - 1/r_2} \qquad (2)$$

where x_1 and x_2 are the effective values of the radius of the capillaries (r_1, r_2) and ρ is the density of the liquid these values differ by less than 1%. Sulfur was found to have a marked surface-active effect on the surface tension of thallium. It is noted that in the elements in the subgroup S, Te and Se the surface tension of the materials decreases with decreasing atomic number, which differs from elements in the I-IV groups, where the surface tension decreases with increasing atomic numbers. Orig. art. has: 3 equations and 1 table.

ASSOCIATION: Institut obshchey i neorganicheskoy khimii im. N. S. Kurnakova Akademii nauk SSSR (Institute of General and Inorganic Chemistry, Academy of Sciences SSSR)

SUBMITTED: 22Nov63   ENCL: 00

SUB CODE: IC, ME   NO REF SOV: 006   OTHER: 004

Card 2/2

ACCESSION NR: AP4019515   S/0076/64/038/002/0325/0330

AUTHOR: Lazarev, V. B. (Moscow)

TITLE: Experimental study of surface tension of indium-antimony system melts

SOURCE: Zhurnal fizicheskoy khimii, v. 38, no. 2, 1964, 325-330

TOPIC TAGS: indium surface tension, antimony surface tension, indium antimonide, indium, antimony, In Sb system, binary metal solution

ABSTRACT: The work was prompted by the scarcity of data concerning surface tension of binary metal solutions especially with regard to a relationship between the shape of their surface tension isotherm and the shape of their state diagram. To investigate this problem, the temperature dependence of surface tension of indium antimony alloys has been determined for the entire range of concentrations from pure indium to pure antimony. The melts were prepared in an atmosphere of purified argon (pressure 100 mmHg) and the Sugden method used with two quartz capillaries of uneven diameter and maximum pressure in the gas bubble. The temperature dependence of the

Card 1/2.

ACCESSION NR: AP4019515

surface tension had been studied – for indium in the 200-800C range –
for antimony in the 650-800C range, and for their alloys-in the 550-
700C range. In all these intervals, antimony is surface-active in
relation to indium. An inflextion in the isotherm of surface tension
shows the existence of their intermetallic compound. The values
of antimony adsorption in indium-antimony melts has been calculated.
In the 550C adsorption isotherm there are two peaks while the mini-
mum corresponds to the intermetallic compound concentration. The
heat of antimony adsorption in these melts has been calculated and
its value is commensurable with the heat of indium antimonide for-
mation. Orig. art. has: 5 figures, 3 formulas, 4 tables.

ASSOCIATION: Institut obshchey i neorganicheskoy khimii im. N. S.
Kurnakova AN SSSR (Institute of General and Inorganic Chemistry,
AN SSSR)

SUBMITTED: 16Nov62

SUB CODE: GC

Card 2/2

DATE ACQ: 31Mar64   ENCL: 00

NR REF SOV: 019   OTHER: 011

L 14457-65   EPA(s)-2/EWT(m)/EPF(n)-2/EWP(t)/EWP(b)   Pt-10/Pu-4   ASD(a)-5/SSD/
AFWL/ASD(m)-3/AS(mp)-2/ESD(gs)   WW/JD/JG
ACCESSION NR: AP4046083   S/0076/64/038/009/2265/2267

AUTHOR: Lazarev, V.B.

TITLE: The temperature dependence of surface tension and the critical
       temperatures of certain metals

SOURCE: Zhurnal fizicheskoy khimii, v. 38, no. 9, 1964, 2265-2267

TOPIC TAGS: surface tension, surface tension temperature function,
liquified metal, critical temperature, mercury, cesium, sodium,
bismuth, lead, thallium, indium, tin, surface tension thermal co-
efficient

ABSTRACT: Based on graphical representations of the temperature-
liquid and saturated vapor density relationships of metals, especial-
ly from works by J. Bender (Phys. Zeitschr., 16, 246, 1915; 19,
410, 1918) and A.V. Grosse (J. Inorg. and Nucl. Chem, 22, No. 12, 23,
1961), it was proposed that the thermal coefficient of the surface
tension of metals decreases (i.e., the absolute value of $\frac{\partial \sigma}{\partial T}$ in-
creases) with increasing temperature. As the temperature approaches
the critical point, the liquid density- and the saturated vapor
Card 1/2

L 14457-65
ACCESSION NR: AP4046083

density-temperature relationship is no longer linear; the sharp
decrease in the degree of difference between the phases results in
the increase in $\frac{d\sigma}{dT}$. The σ-temperature function is linear at temper-
atures
near the fusion temperature of the metals: $\sigma = 484.07 - 0.212t -$
$0.0000946t^2$ (t = degrees C). By extrapolating the σ-temperature
curves to $\sigma = 0$, critical temperatures of the following metals were
qualitatively evaluated (degrees K): mercury 1678, cesium, 1773,
sodium 2280, bismuth 5550, lead 4350, thallium 6400, indium 7000,
tin 7400. These values may be high and should be considered as the
upper limit of possible critical temperature values. Orig. art. has:
1 table and 2 figures

ASSOCIATION: Akademiya nauk SSSR Institut obshchey i neorganiches-
koy khimii im. N.S. Kurnakova (Academy of Sciences SSSR Institute of
General and Inorganic Chemistry)

SUBMITTED: 20Jun63   ENCL: 00

SUB CODE: MM, TD   NR REF SOV: 013   OTHER: 004
Card 2/2

ACCESSION NR: AP4040958

8/0020/64/156/005/1159/1162

AUTHOR: Lazarev, V. B.

TITLE: Analysis of adsorption layers on molten germanium surface

SOURCE: AN SSSR. Doklady*, v. 156, no. 5, 1964, 1159-1162

TOPIC TAGS: germanium, molten germanium, germanium adsorption layer, semiconductor, solid state physics, gallium, indium, thallium, bismuth, antimony, germanium surface tension, crystallography

ABSTRACT: The authors studied the effects of metals from the third and fifth groups of the periodic table upon the surface tension of germanium. These included Ga, Tl, Sb, Bi, and In. Work was carried out because it is of interest to study the adsorption layers which are formed when surface active substances are added to a semiconductor in order to create a specific type of conductivity. The authors point out that a direct analysis of surface active properties on a crystal is an extremely complex process under experimental conditions, and that this problem has not been completely resolved as yet. The surface properties of the above-mentioned metals were studied on the surface of liquid germanium. The surface tension σ of the metal solutions was measured by the technique of maximum pressure in a gas bubble with the use of two sharp-pointed capillaries of

Card 1/4

ACCESSION NR: AP4040958

different diameter which were immersed in the melt at an identical depth. The measurements were carried out in accordance with a procedure outlined by Yu. M. Shashkov and T. P. Kolesnikova (Zh. F. Kh., 37, (1963), 1397). A special instrument was also devised which enables σ to be measured for a number of metals of varying concentration without disturbing the instrument's airtightness. A diagram of this instrument is shown in Figure 1 of the Enclosure. The surface tension measurements of Ge-Ga, Ge-In, Ge-Th and Ge-Bi solutions were carried out over a temperature range of 950-1150C with a concentration of the second component ranging from 0 to 6 at .%. The surface tension of Ge-Sb melts was measured over a temperature range of 950-1100C. All impurities which were tested, with the exception of gallium, lower the germanium surface tension, although the quantitative surface activity of Bi, Th, In and Sb on Ge differs greatly. Bi and Sb have the highest degree of surface activity on Ge, while In and Ga have the lowest. Considering that the surface activity of the metals upon germanium increases according to the series Ga - In - Th - Sb - Bi, the agreement of this sequence with the change in the difference of the atomic volume of these metals and Ge should be noted. Apparently, a good criterion for the surface tension is the magnitude of the differences of the surface tensions of the solvent and impurity. The greater this value, the higher is the surface activity. In computing these differences, the value for the surface tension should not be

Card 2/4

ACCESSION NR: AP4040958

taken at the melting point but at that temperature for which the surface activity
is determined. Surface tension is a thermoclynamic magnitude characterizing, in
a definite degree, the molecular force field of a substance in a condensed state.
Hence, the difference of the surface tensions can be examined as a characteristic
of the degree of difference of the molecular force fields. Orig. art. has: 4
figures and 1 table.

ASSOCIATION: Institut obshchey i neorganicheskoy khimii. im. N. S. Kurnakova
Akademii nauk SSSR (Institute of general and inorganic chemistry, Academy of
Sciences SSSR)

SUBMITTED: 12Feb64

SUB CODE: SS, MM   NO REF SOV: 012

ENCL: 01

OTHER: 001

Card 3/4

ACCESSION NR: AP4040958

ENCLOSURE: 01

1 - sylphon bellows; 2 - ring; 3 - crucible containing metal to be tested; 4 - heater; 5 - 2 capillary tubes of different diameter

Card 4/4

L 40976-65   EWT(m)/EWA(d)/T/EWP(t)/EWP(z)/EWP(b)   Pad   IJP(c)   JD/HM

ACCESSION NR: AP5006419   S/0062/65/000/001/0170/0172

25
B

AUTHOR: Lazarev, V. B.; Dashevskiy, M. Ya.

TITLE: Surface tension of fusions of germanium-antimony and germanium-nickel

SOURCE: AN SSSR. Izvestiya. Seriya khimicheskaya, no. 1, 1965, 170-172

TOPIC TAGS: germanium, antimony, nickel, germanium alloy, surface tension

ABSTRACT: The surface tension of germanium-antimony and germanium-nickel melts was measured and the adsorption of antimony on the germanium surface was calculated. Relationships were found between the solubility and distribution ratios of the dopants and between the dopant solubility and the surface tensions of solvent and additive. Orig. art. has: 2 tables, 2 figures.

ASSOCIATION: Institut obshchey i neorganicheskoy khimii im. N. S. Kurnakova Akademii nauk SSSR (Institute of General and Inorganic Chemistry, Academy of Sciences SSSR)

SUBMITTED: 26May64   ENCL: 00   SUB CODE: MM, IC

NO REF SOV: 006   OTHER: 001

Card 1/1

EPA(bb)-2/EWP(b)/EWA(c)/EWP(t)   Pf-4/Pab-10/Pr-4/Ps-4/Pt-4/Pu-4   IJP(c)   JD/WW/
HM/JG/WH

ACCESSION NR: AP5010977   UR/0286/65/000/007/0165/0165

AUTHOR: Lazarev, V. B.; Pershikov, A. V.

TITLE: Tinning of silicon and ceramic articles. Class 49, No. 169986

SOURCE: Byulleten' izobreteniy i tovarnykh znakov, no. 7, 1965, 165

TOPIC TAGS: tinning, silicon tinning, ceramics tinning

ABSTRACT: This Author Certificate introduces a method of tinning silicon and ceramic articles. In order to obtain a vacuum-tight tin layer, the articles to be tinned are placed on a tantalum mandrel, vacuum degassed (10^{-4} mm Hg) at 950—1100C, and then dipped for a short time in a tin bath placed in the same furnace. In a modification of this method, tinning is done in the furnace with a tantalum soldering gun.   [WW]

ASSOCIATION: none

SUBMITTED: 18Feb63   ENCL: 00   SUB CODE: MM, MT

NO REF SOV: 000   OTHER: 000   ATD PRESS: 4005
Card 1/1

L 34500-65   EWT(m)/EPF(c)/EPR/EWP(t)/EWP(b)   Pr-4/Ps-4   IJP(c)   JD/JG
ACCESSION NR: AP5002797   S/0078/65/010/001/0022/0026

AUTHOR: Lazarev, V. B. ; Tsylov, Yu. A.

TITLE: Surface tension of some nitrate solutions of rare earth elements and of
aluminum

SOURCE: Zhurnal neorganicheskoy khimii, v. 10, no. 1, 1965, 22-26

TOPIC TAGS: surface tension, Rehbinder apparatus, lanthanum nitrate, neody-
mium nitrate, aluminum nitrate, tributylphosphate, metaxylene

ABSTRACT: The surface tension (σ) of aqueous solutions of $La(NO_3)_3$ and
$Nd(NO_3)_3$ and of these solutions containing $Al(NO_3)_3$, tributyl phosphate (TBP),
metaxylene or TBP-metaxylene mixtures was measured using a modified
Rehbinder apparatus (Z. Phys. Chem. 111, 447 (1924)). The dependence of σ of
aqueous solutions of rare earth element nitrates on their concentration c (from
50-250 g/l) and on temperature t (20-60C) was found:
$$\sigma = 75.02 + 2.775.10^{-2}c - 0.148t$$
The La, Nd and Al nitrates are surface-inactive with respect to water; the value

Card 1/2

L 34500-65
ACCESSION NR: AP5002797

of their surface activity, which is negative, increased in absolute value with increase in temperature. The σ-t relationships for TBP, metaxylene and their mixtures were determined: $\sigma_{TBP} = 29.46 - 0.067t$; $\sigma_{m-xylene} = 30.57 - 0.097t$. At 40C σ was independent of the composition of mixtures of TBP and metaxylene. The σ of TBP and some of the TBP-metaxylene mixtures in equilibrium with $La(NO_3)_3$ was found to be a complex function of all 3 components of the system. Orig. art. has: 6 tables and 1 figure.

ASSOCIATION: Institut obshchey i neorganicheskiy khimii im. N. S. Kurnakova Akademii nauk SSSR (Institute of General and Inorganic Chemistry Academy of Sciences SSSR)

SUBMITTED: 19May64   ENCL: 00   SUB CODE: GC

NR REF SOV: 012   OTHER: 002

Card 2/2

L 34979-65   EPA(s)-2/EWT(m)/EPF(n)-2/EWA(d)/T/EWP(t)/EWP(b)   Pt-10/Pu-4   IJP(c)
JD/WW/JG

ACCESSION NR: AP5004353   S/0076/65/039/001/0072/0078

AUTHOR: Lazarev, V. B.

TITLE: Surface phenomena in molten germanium alloys

SOURCE: Zhurnal Fizicheskoy khimii, v. 39, no. 1, 1965, 72-78

TOPIC TAGS: germanium alloy, surface tension, adsorption, germanium surface

ABSTRACT: Since the adsorption of various substances on the surface of a semi-
conductor changes its electrical and physical properties, it is of interest to
investigate the adsorbed layers formed on the outer boundary of the semiconductor
by surface active impurities. The goal of this work was to study the effect of
antimony, bismuth, indium, gallium and thallium on the surface tension of ger-
manium since some of these elements are used for doping germanium. The maximum
bubble pressure method was used for measurement of the surface tension σ of
metallic solutions. The measurements were made in the 950-1150°C range with con-
centration of the second component varying from 0 to 6 atom %. The surface ten-
sion of Ge-Sb melts was measured in the 950-1100°C range. The amounts of Bi, Sb,
Tl, In and Ga adsorbed on the germanium surface layer were determined. The sur-
face area of the atoms of these adsorbed metals was calculated. In terms of the

Card 1/2

L 34979-65

ACCESSION NR: AP5004353

impurity concentrations now being realized in the semiconductor industry, the adsorption layers formed by Bi, Sb, Tl and In on the germanium surface were not even close to the saturation point. The experimental data were compared with the surface activity criteria for metals which are available in the literature. It is suggested that the difference in the surface energies of two metals may be used to find the difference in their molecular force fields. Orig. art. has: 7 tables and 4 figures.

ASSOCIATION: Institut obshchey i neorganicheskoy khimii im. N. S. Kurnakova, Akademiya nauk SSSR (Institute of General and Inorganic Chemistry, Academy of Sciences SSSR)

SUBMITTED: 12Feb64   ENCL: 00   SUB CODE: MM

NO REF SOV: 017   OTHER: 001

Card 2/2

LAZAREV, V.B.; MALOV, Yu.I.

Experimental study of the extrinsic photoeffect from the surface
of diluted potassium amalgams in the liquid and solid states.
Dokl. AN SSSR 161 no.4:875-877 Ap '65.   (MIRA 18:5)

1. Institut obshchey i neorganicheskoy khimii im. N.S.Kurnakova
AN SSSR. Submitted October 5, 1964.

L 4398-66   EWT(m)/EWP(t)/EWP(b)   IJP(c)   JD/JG
ACCESSION NR: AP5025867   UR/0020/65/164/004/0846/0848

AUTHOR: Lazarev, V. B.; Malov, Yu. I.

TITLE: Photoelectric phenomena in dilute alkali metal amalgams

SOURCE: AN SSSR. Doklady, v. 164, no. 4, 1965, 846-848

TOPIC TAGS: photoelectric effect, sodium amalgam, potassium, cesium, work function, adsorption

ABSTRACT: Photoemission currents from the surface of mercury-sodium solutions containing from 0 to 0.7 at% sodium and mercury-cesium solutions containing from 0 to 0.001 at% cesium were measured between +25 and -80°. A plot of the photoemission currents versus the alkali metal concentration for the same wavelength of incident light (3136 Å) showed the external photoelectric effect from the surface of cesium amalgams to be much greater than that from potassium amalgams and still greater than that from sodium amalgams. After determining the electron work functions ϕ, the authors compared them with reported data on the surface tension σ of these amalgams; the curves representing the concentration dependence of σ and ϕ were found to be similar. A study of the temperature dependence of photocurrents

Card 1/2

L 4398-66
ACCESSION NR: AP5025867

for the sodium, potassium, and cesium amalgams showed a marked increase in photo-emission current, and a shift of the "red boundary" of the photoelectric effect toward longer wavelengths. This behavior or the temperature dependence may be ex-plained by an increasing absorption of the alkali metal with decreasing tempera-ture. Orig. art. has: 4 figures.

[14]

ASSOCIATION: Institut obshchey i neorganicheskoy khimii im. N. S. Kurnakova Akademii nauk SSSR (Institute of General and Inorganic Chemistry, Academy of Sciences, SSSR)

SUBMITTED: 26Feb65   ENCL: 00   SUB CODE: GC, OP

NO REF SOV: 008   OTHER: 000   ATD PRESS: 4/96

Card 2/2

L 11001-66   EWT(m)/EWP(t)/EWP(b)   IJP(c)   JD

ACC NR: AP5028720   SOURCE CODE: UR/0363/65/001/011/1901/1910

AUTHOR: Lazarev, V. B.; Dashevskiy, M. Ya.

ORG: Institute of General and Inorganic Chemistry im. N. S. Kurnakov, Academy of
Sciences SSSR (Institut obshchey i neorganicheskoy khimii Akademii nauk SSSR); Ins-
titute of Metallurgy im. A. A. Baykov (Institut metallurgii)

TITLE: Surface phenomena and crystallization processes in doped indium antimonide al-
loys

SOURCE: AN SSSR. Izvestiya. Neorganicheskiye materialy, v. 1, no. 11, 1965, 1901-
-1910

TOPIC TAGS: indium compound, antimonide, selenium, tellurium, germanium, surface
tension, chemical absorption, metal crystallization, alloy, crystal growth

ABSTRACT: The effect of selenium, tellurium, and germanium on the surface tension
of indium antimonide melts was studied, and it was shown that Se and Te are absorbed
at the interface, whereas practically no absorption of germanium occurs. Differences
in the growth of indium antimonide dendrites from melts doped respectively with Se
and Te are due to the different absorbability of these substances on indium antimo-
nide. A new method is proposed for estimating the effective generalized moments of
elements and compounds, and it is shown that the structure of melts can be evaluated

Card 1/2   UDC: 546.682'861:532.6

L 11001-66

ACC NR: AP5028720

by using data on their surface tension and the concept of the generalized moment. It is suggested that the difference in the surface tension of two substances be used to characterize the difference in their molecular force fields. The relationships between the solubility of impurities, coefficients of their distribution, and diffusion constants and the difference in the surface tension of the solvent and additive are presented. In conclusion, the authors thank M. S. Mirgalovskiy for his continued interest and participation in the discussion of the results, and N. Ye. Il'in and A. V. Pershikov for assistance in the experiments. / Orig. art. has: 10 figures, 2 tables, 4 formulas.

SUB CODE:20,11,07/   SUBM DATE: 05Jul65/   ORIG REF: 016/   OTH REF: 008

Card 2/2

LAZAREV, V.B. (Moskva)

Surface phenomena in molten germanium alloys. Zhur. fiz. khim.
39 no. 1:72-78 Ja '65   (MIRA 19:1)

1. Institut obshchey i neorganicheskoy khimii imeni N.S. Kur-
nakova AN SSSR. Submitted February 12, 1964.

LAZAREV, V.B.; PERSHIKOV, A.V.

Improved Rebinder instrument for measuring surface tension.
Zhur. fiz. khim. 39 no.6:1528-1529 Je '65.   (MIRA 18:11)

1. Institut obshchey i neorganicheskoy khimii imeni Kurnakova.
Submitted Feb. 12, 1964.

ACC NR: AR6035419   SOURCE CODE: UR/0137/66/000/009/G052/G052

AUTHOR: Dashevskiy, M. Ya.; Mirgalovskaya, M. S.; Lazarev, V. B.

TITLE: Growing of indium antimonide crystals from melts doped with surface-active and surface-inactive additives

SOURCE: Ref. zh. Metallurgiya, Abs. 9G364

REF SOURCE: Sb. Poverkhnostn. yavleniya v rasplavakh i voznikayushchikh iz nikh tverd. fazakh. Nal'chik, 1965, 579-584

TOPIC TAGS: indium compound, antimonide, surface active agent, single crystal growing, surface tension, dendrite

ABSTRACT: A description is presented of a combined setup for growing of single crystals drawn from the melt and measuring the surface tension of the melt. Measurement of the surface tension of a melt of InSb doped with Ge or Se has shown that the Se is surface-active (it is adsorbed) while the Ge is surface-inactive (is not adsorbed) as an additive. Single crystals and dendrites of InSb were drawn from melts doped with germanium in the range 0.05 - 2.5 at.% and Se 0.024 - 0.25 at.%. With increasing Ge concentration in the melt, the width of the dendrite ribbons decreased. No noticeable influence of Ge on the growth of the single crystal was noted. Dendrites with large Si content could not be grown, for their growth stopped at 0.25 at.% Se. No morphological differences were noted between single crystals grown from melts alloyed with Se or Ge. The dependence of the supercooling of the InSb melt on the Ge or Se con-

Card 1/2   UDC: 621.315.592

ACC NR: AR6035419

centration shows that at these concentrations the Ge and Se have little influence on
the value of the supercooling. (From RZh Fiz.) [Translation of abstract]

SUB CODE: 20

Card 2/2

ACC NR: AR7000837   SOURCE CODE: UR/0058/66/000/009/A049/A049

AUTHOR: Dashevskiy, M. Ya.; Mirgalovskaya, M. S.; Lazarev, V. B.

TITLE: Growing single indium antimonide crystals from melts doped with surface-active and surface-inactive impurities

SOURCE: Ref. zh. Fizika, Abs. 9A415

REF SOURCE: Sb. Poverkhnostn. yavleniya v rasplavakh i voznikayushchikh iz nikh tverd. fazakh. Nal'chik, 1965, 579-584

TOPIC TAGS: crystal, crystal growth, crystal impurity, indium antimonide, crystallography, surface active alloy, surface inactive alloy, surface active impurity, surface inactive impurity, impurity, semiconductor crystal, germanium alloy, selenium alloy, doping

ABSTRACT: A description is given of a device for growing monocrystals (C) by pulling them from a melt (M), and for measuring surface tension of M. Measurements of surface tension of M in InSb doped with Ge and Se showed that Se is a surface-active impurity, and that Ge is a surface-inactive impurity. Monocrystals

Card 1/2

ACC NR: AR7000837

and dendrites from M [sec] were grown, alloyed with Ge in the amount of 0. 05 —
2. 5 at % and with Se in the amount of 0. 0024 — 0. 25 at %. An increase in the con-
centration of Ge in the M was accompanied by a decrease in the width of dendrite
strips. No particular effect of Ge on the growth of C was noted. No success was
achieved in growing dendrites containing large amounts of Se, since at 0. 25 at %
of Se their growth ceases. No morphological differences were noted between C
grown from M and alloyed with Se and K grown from P and alloyed with Ge. It
was shown that within the given range of concentrations, Ge and Se affect the
process of supercooling only slightly. G. Volkov. [Translation of abstract]

[SP]

SUB CODE: 20/

Card 2/2

ACC NR:
AR7000855

SOURCE CODE: UR/0058/66/000/009/E008/E008

AUTHOR: Lazarev, V. B.; Dashevskiy, M. Ya.

TITLE: Study of surface phenomena in melts of semiconductors

SOURCE: Ref. zh. Fizika, Abs. 9E68

REF SOURCE: Sb. Poverkhnostn. yavleniya v rasplavakh i voznikayushchikh iz nikh tverd. fazakh. Nal'chik, 1965, 383-388

TOPIC TAGS: germanium semiconductor, semiconductor melt,   selenium, thallium, antimony, atom, gallium, surface tension, surface phenomenon, impurity

ABSTRACT: A study is made of the influence of Sb, Bi, In, Ga and Tl impurities on the surface tension (σ) of Ge; and of Se, Tl and Ge on σ of indium antimonide. It was found that except for Ga, all additions mentioned lowered σ of Ge. In the case of InSb, Ge was surface-neutral. It was also found that the values of the limit surface activity of the investigated impurities were highest when their σ was the lowest, by comparison with Ge and InSb. It is shown that

Card 1/2

ACC NR, AR7000855

there is a regular relationship between one of the most widely used criteria of surface activity — the generalized moment (m) and σ. The established relationship $m = f(\sigma)$ is used to determine the effective value of m for individual metals and for InSb, as well as to determine the degree of ionization of atoms of the substances in their own melt. N. Pokrovskiy. [Translation of abstract] [GC]

SUB CODE: 20/1

Card 2/2

ACC NR: AP7005591

AUTHOR: Dashevskiy, M. Ya; Kukuladze, G. V.; Lazarev, V. B.; Mirgalovskaya, M. S.

SOURCE CODE: UR/0020/67/172/002/0403/0406

ORG: Metallurgy Institute im. A. A. Baykov, Academy of Sciences, SSSR (Institut metallurgii Akademii nauk SSSR); Institute of General and Inorganic Chemistry im. N. S. Kurnakov, Academy of Sciences, SSSR (Institut obshchey i neorganicheskoy khimii Akademii nauk SSSR)

TITLE: Surface phenomena and crystallization processes in gallium antimonide melts

SOURCE: AN SSSR. Doklady, v. 172, no. 2, 1967, 403-406

TOPIC TAGS: surface tension, gallium compound, antimonide, crystallization

ABSTRACT: In order to determine the general applicability of the regularities characterizing the relationship between surface phenomena and crystallization processes in indium antimonide melts, the following phenomena were investigated: surface tension of melts of the gallium-antimony system, influence of zinc and tellurium on the surface tension of gallium antimonide, and influence of these admixtures on the supercooling of Ga-Sb melts and on the growth of crystals from the melts. It is suggested that the behavior of the impurities in the solvent melt can be predicted from the difference of surface tensions in the case of type $A^{III}Sb$ antimonides. In $A^{III}B^{V}$ compounds which crystallize in a zinc-blende-type lattice, a correlation exists between the mean atomic number of the compound and the surface tension at the

Card   1/2

UDC: 546.682'861:532.6

ACC NR: AP7005591

melting point: the higher the mean atomic number, the lower the surface tension of the compound. Data on the effect of Te on the supercooling of indium antimonide indicate that surface-active admixtures increase the probability of formation of a solid phase nucleus. At a certain concentration of Te, the growth of lamellar dendrites of gallium antimonide was hindered, causing distorted dendrites to grow, then was stopped altogether as the Te content increased further. The introduction of zinc in appreciable amounts did not interfere with the growth of lamellar dendrites of gallium antimonide. The regularities found by studying the role of surface phenomena in the crystallization of indium antimonide melts were found to apply to gallium antimonide as well, and are therefore thought to cover at least all compounds of type $A^{III}B^V$ which crystallize in a zinc-blende-type lattice. The paper was presented by Academician Sazhin, N. P., 4 Apr 66. Orig. art. has: 3 figures and 1 table.

SUB CODE: 11,20/ SUBM DATE: 04Apr66/ ORIG REF: 009/ OTH REF: 001

2/2

LAZAREV, V.D., inzh; TSAL', M.A., inzh.

Overall mechanization and automation of hardware production.
Mekh. i avtom. proizv. 17 no.4:3-5 Ap '63.   (MIRA 17:9)

S/196/61/000/011/002/042
E194/E155

AUTHORS: Levin, A. I., and Lazarev, V. F.

TITLE: The use of alternating current in forming lead
            accumulator plates

PERIODICAL: Referativnyy zhurnal, Elektrotekhnika i energetika,
            no.11, 1961, 20, abstract 11A 117. (Vestn. elektroprom-
            sti,3/no.6, 1961, 60-62)

TEXT: The effects that result from superposing a.c. on d.c.
in the process of forming lead accumulator plates were
investigated. The a.c. current density was 0.715 A/dm2, while
the d.c. current density ranged from 0.715 to 4.29 A/dm2. The
ratio of direct to alternating current density was maintained
constant and greater than 1 during each test. The paste for the
positive electrode was made of litharge and red lead and that for
the negative of lead powder. It was found possible to increase
the direct-current density by a factor of 2 - 3 as compared with
the value normally used in production and to cut the forming time
from 15-18 to 5-6 hours without appreciably increasing the
temperature. If the d.c. is more than 3 times the a.c. component
Card 1/2

The use of alternating current ...   S/196/61/000/011/002/042
                                            E194/E155

there is, however, a notable diminution in the effectiveness of
the plate-forming conditions with change in the direction of
current. With the above mentioned ratio of current densities
the a.c. has no appreciable influence on the electro-chemistry,
chemical composition or porosity of the active substance of
starter accumulator plates but appreciably increases their
mechanical strength.
3 literature references.

[Abstractor's note: Complete translation.]

Card 2/2

LEVIN, A.I.; LAZAREV, V.F.

ChM foam-producing agent and its effect on the formation of lead
plates of a storage battery. Zhur.prikl.khim. 35 no.1:123-127 Ja
'62.
                                                    (MIRA 15:1)

1. Ural'skiy politekhnicheskiy institut imeni S.M.Kirova.
      (Surface-active agents)   (Electrochemistry)
                    (Storage batteries)

LAZAREV, V.F.; LEVIN, A.I.

Nature of the polarization in the formation of lead from lead
sulfate. Zhur. fiz. khim. 36 no.6:1318-1320 Je'62
(MIRA 17:7)

1. Ural'skiy politekhnicheskiy institut imeni Kirova.

LEVIN, A.I.; LAZAREV, V.F.; MUKHIN, V.A.

Electrolytic lead coating of auxiliary parts of a storage battery using sulfamine electrolytes. Zhur. prikl. khim. 38 no.7:1569-1574 Jl '65.
(MIRA 18:7)

1. Ural'skiy politekhnicheskiy institut.

LAZAREV, V.F.; OVCHARENKO, V.I.; LEVIN, A.I.; RUDOY, V.M.

Effect of surface active substances on the process of passivation of a lead electrode. Zhur.prikl.khim. 38 no.6:1305-1309 Je '65. (MIRA 18:10)

1. Ural'skiy politekhnicheskiy institut imeni S.M.Kirova.

LAZAREV, V. G.

Lazarev, V. G., Levitina, G. A., and Magnitskiy, A. N.   "Changes in subordination in traumas of the peripheral nervous system", in the collection: Subordinatsiya v nervnoy sisteme i yeye znacheniye v fiziologii i patologii, Moscow, 1948, p. 100-09.

SO: U - 3042, 11 March 53, (Letopis "Zhurnal "nykh Statey, No. 7, 1949)

LAZAREV, V. G.,

Verzilova, C. V., Lazarev, V. G., and Magnitskiy, A. N. "Changes in subordination in brain trauma", in the collection: Subordinatsiya v nervnoy sisteme i yeye znacheniye v fiziologii i patologii, Moscow, 1948, p. 110-22, - Bibliog: 7 items.

SC: U - 3042, 11 March 53, (Letopis "Zhurnal "nykh Statey, No. 7, 1949)

LAZAREV, V. G.

USSR/ Molecular theory

Card 1/1   Pub. 22 - 9/46

Authors   : Lazarev, V. G. Act. Mem. Acad. Scs., and Ovcharenko, O. N.

Title   : About the effect of crystallic lattice holes on the electric
              resistance of a metal

Periodical : Dok. AN SSSR 100/5, 875-878, Feb 11, 1955

Abstract   : The results of experiments with the electric conductivity are
              described and analyzed. The experiments were conducted for the
              purpose of establishing the correctness of the theory dealing
              with the effect of the so-called crystal lattice holes on the
              electric conductivity of metals.*) Eleven references: 2 French,
              6 USA, 2 USSR and 1 German (1931-1953). Graphs.

Institution : Academy of Sciences of the USSR, Physico-Technical Institute

Submitted   : .....

              *) In the abstracted article, the R is used as the universal
              constant and as a metal resistance.

$\mathcal{L} \mathcal{A} \mathcal{L} \mathcal{A} \mathcal{L} \mathcal{L} \, \mathcal{V} \quad \mathcal{V} \quad \omega$

112-1-2396 D

Translation from: Referativnyy Zhurnal, Elektrotekhnika, 1957,
Nr 1, p. 349 (USSR)

AUTHOR: Lazarev, V.G.

TITLE: Methods of Objective Evaluation of the Principles of
             Constructing an All-Relay System for the Automatic Office
             (on the Example of a Relay Telephone Substation) [Metodika
             ob''yektivnoy otsenki printsipov postroyeniya releynykh
             ustroystv ATC (na primere releynoy telefonnoy podstantsii)]

ABSTRACT: Bibliographic entry on the author's dissertation for the
             degree of Candidate of Technical Sciences, presented to
             the Moscow Electrical Communications Engineering Institute
             (Mosk.elektrotekhn. in-t svyazi), Moscow, 1956.

ASSOCIATION: Moscow Electrical Communications Engineering Institute
             (Mosk.elektrotekhn. in-t svyazi, Moscow)

Card 1/1

LAZAREV, V.G.

Determining the minimum number of intermediate relays in designing
multicontact circuits. Sber.nauch.rab.po prov.sviazi. no.5:93-103
'56.   (Electric relays)   (MIRA 9:9)

LAZAREV, V. G.

"The Method of Determiningthe Minimum Relay Number."

report presented at All-Union Conference on Problems in the Theory of Relay Devices, Inst. for Automation and Remote Control AN USSR, 3-9 Oct 1957. Vestnik AN SSSR, 1958, No. 1, v. 28, pp. 131-132. (author Ostianu, V. M.)

ARKHANGEL'SKAYA, A. A., LAZAREV, V. G. and ROGINSKIY, V. N.

"A Machine for the Synthesis of Contact Poles."

report presented at All-Union Conference on Problems in the Theory of Relay Devices,
Inst. for Automation and Remote Control AN USSR, 3-9 Oct 1957.
Vestnik AN SSSR,   1958, No. 1, v. 28, pp. 131-132.   (author Ostianu, V. M.)

LAZAREV, V. G.

Bond Offer.,

All-Union Conference on the Theory of Relay Systems,
(Vsesoyuznoye soveshchaniye po teorii ustroystv releynogo
deystviya).

PERIODICAL: Izvestiya Akademii Nauk SSSR, Otdeleniye Tekhnicheskikh
Nauk, 1958, No.2, pp. 167-168 (USSR).

ABSTRACT: The Institute of Automation and Telemechanics of the Ac.
Sc. USSR (Institut Avtomatiki i Telemekhaniki Akademii
Nauk SSSR) convened in October, 1957 an All Union
Conference on the theory of relay systems. The aim of
the conference was to evaluate the present state of the
problem of the theory of relay operation, particularly
evaluation of the problems of synthesis, analysis, and
transformation of the structure of relay equipment,
optimum construction and assembly of such structures,
automation of the processes of synthesis and analysis
of such structures. Over 330 representatives of research
establishments, works' laboratories and project organiza-
tions from numerous centres of the USSR as well as
scientists from Roumania, Hungary and Czechoslovakia
participated in the conference.
Card 1/5 In his opening address M. A. Gavrilov reported on the

... Conference on the Theory of Relay Systems, 24-2-28/28 ... present state and the main trends of development of the theory of relay circuits. Thirty papers were read including "On the Development of Mathematical Logic and its Engineering Applications" by S. A. Yanovska, "Algebraic Theory of the Operation of Relay-Contact Circuits" by Gr. K. Moisil (Bucharest), "On the Inversion Complexity of a System of Functions" by A. A. Markov, "Minimum Disjunctive Shape of "Bull" Functions" by K. Popovich (Bucharest), "On Certain Mathematical Problems of the Theory of Relay Circuits" by S. V. Yablonskiy.

The technique of operation in this field was ... in the following papers: "Technique of Determining the Minimum Number of Relays Necessary for the Construction of a Relay Circuit with Given Conditions of Operation" V. G. Lazarev; "Matrix Method and Method of Obtaining ... Functions in the Theory of Contact Circuits" by ... "On the Theory of Synthesis of Contact Circuits" by F. Svobodin (Prague); "Construction of Relay Circuits with Bridge Connections" by M. A. Gavrilov; "Method of Synthesis of Multi-Pole Relay-Contact Circuits" by V. N. Grabenshchikov; "Application of the Method of ...

Conference on the Theory of Relay Systems

investigation of symbolic recording of the conditions
of operation for determining the existing relations and
particularly for developing methods of sub-dividing the
general sequences into sequences corresponding to the
various functions to be fulfilled and synthesis of relay
equipment in sections. In some cases, the statistical
characteristics of individual connections being taken
has to be taken into consideration. An important task
of the theory of relay systems is that of minimizing the
size of their structure. In view of the complexity of
the structures of modern relay systems it is of great
importance to develop automatic machinery for synthesis
and analysis of relay apparatus and the first successes
achieved in this field were reported on at the conference.
The Institute of Automatics and Telemechanics, Ac.Sc.
USSR has developed a universal machine for analysing
the structure of relay systems on twenty relays, "LUMS",
which permits solution of a very wide class of problems.
In the Computer Institute of the Czechoslovak Ac.Sc. and
in the Laboratory of Problems of Wire Communication of the
Card 4/5   Ac.Sc. USSR, the first machines were built for synthesis

of structural activity indices. This opens up the further development, particularly in respect of methods for the synthesis of structures. The members of the conference pointed out the advisability of organizing a coordinating commission relating to work on the theory of relay systems and of establishing an international federation relating to this problem.

AUTHORS: Lazarev, V. G., Sagalovich, Yu. L. (Moscow) 103-19-5-0/14

TITLE: On a Certain Type of Commutation Circuits
               (Ob odnom tipe kommutatsionnykh skhem)

ABSTRACT: Beside the general methods for the synthesis of relay-
               -contact-circuits (References 1-4) special methods for
               individual types of circuits exist by means of which
               the projection of the circuit can be considerably simpli-
               fied and accelerated. Such a method for the construction
               of a commutator is suggested here. This method uses some
               data from group theory. The problem of the construction
               of a commutator arose in connection with the elaboration
               of the machine for the synthesis of the contact circuit
               (Reference 6) which models the cascade-method (Reference 3)
               (graphical method - Reference 4). The type of commutation
               circuits investigated here is a circuit of the recomputa-
               tion of dual numbers in various permutations of their place.
Card 1/2   The method of synthesis based upon the employment of the

On a Certain Type of Commutation Circuits   103-19-5-3/14

group-permutation-theory yields the possibility of obtaining optimum circuits with a small expenditure of energy in their composition. The formula for the computation of the number of contacts necessary for the construction of the investigated commutation circuits is given.
There are 2 figures and 7 references, all of which are Soviet.

SUBMITTED: July 8, 1957

AVAILABLE: Library of Congress

1. Mathematical computers--Circuits

Card 2/2

KHARKEVICH, A.D.; ROGINSKIY, V.N.; OPOL'SKAYA, Ye.K.; LAZAREV, V.G.;
SHAPIRO, S.B.; GORYACHEV, V.A.; PARAFONOV, L.S., otv.red.;
BALAKIREV, A.F., red.; KARABILOVA, S.F., tekhn.red.

[Crossbar telephone substation; information collection]
Koordinatnaia telefonnaia podstantsiia; informatsionnyi
sbornik. Moskva, Gos.izd-vo lit-ry po voprosam sviazi i
radio, 1959. 87 p.   (MIRA 13:1)
                    (Telephone, Automatic)

LAZAREV, V G

6(0)   PHASE I BOOK EXPLOITATION   SOV/2793

Akademiya nauk SSSR. Laboratoriya sistem peredachi informatsii

Problemy peredachi informatsii. vyp. 3: Koordinatnyye sistemy ATS (Problems
   of Information Transfer. Nr. 3: Crossbar Systems) Moscow, Izd-vo AN SSSR,
   1959. 147 p. 2,000 copies printed.

Ed. of Publishing House: K. I. Grigorash; Tech. Ed.: T. V. Polyakova;
   Editorial Board: A. A. Kharkevich (Resp. Ed.), V. N. Kuznetsov, I. A.
   Ovseyevich, V. N. Roginskiy (Resp. Ed. of this Number), and V. G. Solomonov
   (Deputy Resp. Ed.).

PURPOSE: This collection of articles may be useful to engineers engaged in the
   design of crossbar automatic telephone systems.

COVERAGE: The authors discuss the principle of operation of crossbar automatic
   telephone systems and their components. They discuss methods of switching
   and using crossbar connectors in selector units and present block diagrams of

Card 1/4

Problems of Information Transfer (Cont.)   SOV/2793

individual units and of the entire automatic telephone system. They also
explain the principle of constructing master-switch circuits and present
methods of calculating losses in systems. Articles 1 and 3 were presented
at the conference of the Wire Communication Section of NTOF i E imeni A. S.
Popov on July 15, 1956. Articles 2, 4 and 5 were presented at the Joint
Session of the Laboratory and Chair of Telephony of MEIS on September 21,
1956, December 11, 1957, and November 23, 1956, respectively. No personal-
ities are mentioned. References appear at the end of each article.

TABLE OF CONTENTS:

    The author presents a general discussion of a number of crossbar
automatic telephone systems developed in various West European
countries and describes the advantages of such systems. There
are 14 references: 6 Soviet (including 1 translation), 7 English and
1 German.

Card 2/4

Problems of Information Transfer (Cont.)   SOV/2793

Kharkevich, A. D. Switching Possibilities of Crossbar Connectors and Their
Use in Selector Units of Automatic Telephone Systems   15
   The author discusses the switching characteristics of a crossbar
   connector and describes methods of using it in telephone circuits. He
   also presents examples explaining the construction of selector units with
   crossbar connectors. There are 10 references: 9 Soviet and 1 English.

Kharkevich, A. D. Block Diagrams of Individual Units and of the Entire
Crossbar Automatic Telephone System   54
   The author discusses the operation of various elements and units of a
   crossbar automatic telephone system and presents methods of constructing
   their block diagrams. He also describes the operation of ARF-10, ARF-50 and
   No.5 crossbar types of systems and presents their block diagrams.
   There are 6 references, all Soviet.

Lazarev, V.G., G. G. Savvin and L. I. Smirnova. Basic Principles of Con-
structing Master-switch Circuits of Crossbar Automatic Telephone systems.   78
   The authors discuss the principles of constructing   master-switch cir-
   cuits for group selector and subscriber selector units of crossbar auto-

Card 3/4

Problems of Information Transfer (Cont.)   SOV/2793

matic telephone systems. A discussion of a master-switch circuit for a
subscriber selector unit is presented only for the case of transposed
connections of subscriber lines. There are 18 references: 11 Soviet and
7 English.

Kharkevich, A. D. - Calculation of the Number of Connecting Devices
in a Crossbar Automatic Telephone System.   115
  The author discusses methods of calculating losses in a multistage
system by   analyzing a two-stage circuit. He also derives formulas
for calculating losses and presents numerical examples. There are 12
references: 7 Soviet and 5 English.

AVAILABLE: Library of Congress

Card 4/4   JP/fal
                                                            12/15/59

LAZAREV, V. G.

· 6(7)   ? ?   PHASE I BOOK EXPLOITATION   SOV/3016

Akademiya nauk SSSR. Laboratoriya sistem peredachi informatsii

Problemy peredachi informatsii. vyp. 1: Postroyeniye skhem i setey
    svyazi. (Problems of Information Transmission. Nr. 1: Design
    of Communications Circuits and Networks) Moscow, Izd-vo AN SSSR,
    1959. 163 p. Errata slip inserted. 2,000 copies printed.

Ed. of Publishing House: G. Ye. Pevzner; Tech. Ed.: A. P. Guseva;
    Editorial Board: A. A. Kharkevich (Resp. Ed.), V. N. Kuznetsov,
    I. A. Ovseyevich, V. N. Roginskiy (Resp. Ed. of this Issue), V. G.
    Solomonov (Deputy Resp. Ed.)

PURPOSE: This collection of articles is intended for specialists
    in communications theory.

COVERAGE: This collection of articles by scientists at the Labora-
    tory of Systems for the Transmission of Information, Academy of
    Sciences, USSR, is a continuation of a series of collections
    published earlier under the title "Sbornik nauchnykh rabot po
    provodnoy svyazi" ("Collection of Scientific Works on Wire
Card 1/8

Problems of Information (Cont.)   SOV/3016

Communications") References are given after each article. A
bibliography on automatic telephone systems (ATS) with crossbar
switches is given in the appendix. This bibliography is con-
sidered to be of special interest in connection with the intro-
duction in the USSR of the crossbar system.

TABLE OF CONTENTS:

    This paper was presented at a session of the Scientific
    and Technical Society of Radio Engineering and Electro-
    communications imeni A. S. Popov on May 10, 1956. The author
    discusses a new method of synthesizing relay circuits pro-
    viding series-parallel and bridge-contact circuits, and a
    method for selecting circuits with a minimum number of
    contacts and with automatic accounting for neutral and

Card 2/8

Problems of Information (Cont.)

SOV/3016

unutilized states. According to the author, this method
in certain cases results in a more efficient use of circuits
than is possible by analytic methods. It also makes possible
mechanization of the synthesis of relay systems. There are
9 references, all Soviet.

Arkhangel'skaya, A. A., V. G. Lazarev, and V. N. Roginskiy.
Apparatus for the Synthesis of Contact Circuits   41
This paper was presented at the Laboratory Seminar on
October 5, 1956. The authors present basic principles of
designing an apparatus for the synthesis of contact (1,k)-
terminal networks. This apparatus was developed at the
Laboratory on the basis of the graphical method. There are
9 references: 8 Soviet and 1 English.

Lazarev, V. G. Methods of Determining the Number of Relays
Necessary for Designing a Relay-Contact Circuit According to
Given Operating Conditions
                                                                     53

Card 3/8

Problems of Information (Cont.)   SOV/3016

This paper was presented at a session of the Scientific and Technical Society of Radio Engineering and Electrocommunications imeni A. S. Popov on May 10, 1956. In this paper, principles are outlined for selecting the minimum number of relays necessary for the synthesis of relay-contact circuits. The minimum number of receiver components and methods of selecting the minimum number of receiving relays are also presented. The author considers the problem of determining the common minimum of receiving and intermediate relays necessary for designing circuits according to given conditions. There are 8 references: 6 Soviet and 2 English.

Kharkevich, A. D.   Selecting a Grouping Lay-out for a Telephone
System Substation
                                                                72
     This paper was presented at a joint session of the
     Laboratory Seminar and Department of Telephony at MEIS
     on June 24, 1953.   The author investigates grouping
     schemes useful in designing small-capacity telephone

Card 4/8

Problems of Information (Cont.)   SOV/3016

system substations with the routing of intercommunications through a regional crossbar system. An evaluation of variations of grouping schemes according to the overall number of connection points is made and the optimum substation grouping scheme is selected and equipped with switching relay-action devices. There are 13 references: 9 Soviet and 4 English

Melik-Gaykazova, E. I., L. I. Smirnova and A. D. Kharkevich.
Experimental Investigation of the Carrying Capacity of the Grouping
Lay-out of a Telephone System Substation   103
   The paper was presented at the Laboratory Seminar on
October 26, 1956. The selection of the grouping scheme
was specified by the authors on the basis of data obtained
from calculations using the method of artificial loading.
The substation had a capacity of 100 numbers, with two
connection stages for outgoing, and three connection
stages for incoming traffic. On the basis of this investi-
gation, the authors determine the most convenient distri-
bution of outgoing trunks among the intermediate switches,

Card 5/8

Problems of Information (Cont.)   SOV/3016

the necessary number of internal trunks between the
incoming and intermediate switches, and the holding sequence
of the internal trunks. There are 7 references, 3 Soviet
and 4 English.

Analysis of Grouping Lay-out of a Telephone System Substation
Using the Method of Probability Graphs   118
This paper was presented at the Laboratory Seminar on
November 23, 1956. A method using probability graphs for
calculating the carrying capacity of complex switching
networks is presented. A telephone substation with two
connection stages for outgoing and with three connection
stages for incoming traffic is investigated using probability
graphs. On the basis of this investigation the author
determines the most convenient graph topology, using cross-
bar trunks in developing substation switching. In an
appendix a new treatment of the probability graph is pre-
sented. There is 1 English reference.

Card 6/8

Problems of Information (Cont.)   SOV/3016

Povarov, G. N. Structural Theory of Communications Networks   126
  This paper was presented at a joint session of the
  Laboratory Seminar and of the Telephony at MEIS
  on January 6, 1956. The fundamentals of mathematical
  analysis of communications networks using matrix algebra
  are presented. Problems in the structural theory of
  communications networks are discussed: calculation of
  the number of tandem trunks between any two stations in
  the network, determination of the length of the longest
  and shortest tandem trunk, of the coherence and compact-
  ness of the network and of some other parameters. The
  relationship between the structural theory of communi-
  cations networks, graphical theory and theory of relay-
  contact circuits is discussed. There are 17 references:
  11 Soviet (including translation) , 4 English and 2
  German.

Kharkevich, A. D. Bibliography on the Swedish Crossbar   141
System

Card 7/8

Problems of Information (Cont.)

SOV/3016

This bibliography with annotations contains a list of 69 articles, company data and books; 29 information notes and 89 Swedish patents.

Work of Laboratory Seminars on the Development of Scientific Problems of Wire Communication of the Academy of Sciences, USSR, 1956

AVAILABLE: Library of Congress

160

Card 8/8

JP/mmh
2-3-60

ARKHANGEL'SKAYA, A.A.; LAZAREV, V.G.; ROGINSKIY, V.N.

Machine for the synthesis of contact circuits. Probl. pered. inform.
no.1:41-52 '59.   (MIRA 13:3)
(Switching theory) (Electric relays)

LAZAREV, V.G.

Method of determining the number of required relays for the design of
contact relay circuits with given operating conditions. Probl. pered.
inform. no.1:53-71 '59.   (MIRA 13:3)
          (Electric relays) (Switching theory)

LAZAREV, V.G.; SAVVIN, G.G.; SMIRNOVA, L.I.

Fundamental principles in the design of controlling units for crossbar automatic telephone exchanges. Probl.pered.inform. no.3:78-114 '59. (MIRA 13:1)

(Telephone, Automatic)

IAZAREV, V.G.; SAGAIOVICH, Yu.L.

Commutator of a machine for synthesis of switching circuits.
Probl. pered. inform. no.4:124-132 '59.   (MIRA 13:7)
        (Telephone, Automatic) (Switching theory)

LAZAREV, V. [G]

report to be presented at the 1st Intl Congress of the Intl Federation of Automatic Control, 25 Jun-5 Jul 1960, Moscow, USSR.